



The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Monday, September 19, 2016** at 12:15 a.m. Eastern Time. Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: <http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=0H300&Standard=061&>

NSF/ANSI 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#). Click here for the definitions of [Water Contact Temperatures denoted in these Listings](#).

Taco, Inc.

1160 Cranston Street
Cranston, RI 02920
United States
401-942-8000

Facility : Fall River, MA

Mechanical Devices

Trade Designation	Size	Water Contact Temp	Water Contact Material
Thermal Expansion Tanks [G]			
CA\$- & -@P[1] [2] [3] [4]	90 L - 10,000 L	CLD 23	MLTPL
PAX#- %-@P[1] [4] [5] [6]	30 L - 500 L	CLD 23	MLTPL

[1] Certified for use on cold water side of the hot water tank only.

[2] \$ is the tank size in liters and may be 90, 140, 215, 300, 450, 500, 600, 700, 800, 900, 1000, 1100, 1200, 1300, 1400, 1500, 1600, 1800, 2000, 2500, 3000, 4000, 5000, 7500 or 10,000.

[3] & is the pressure rating and may be 125, 150, 175, 250, or 300.

[4] @ is optional and may be the letter A, B, or AB indicating additional tank options.

[5] # is the tank size in liters and may be 30, 42, 84, 130, 170, 215, 254, 300, 350, 425, or 500.

[6] % is the pressure rating and may be 150 or 175.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility : Cranston, RI

Mechanical Devices

Trade Designation	Size	Water Contact Temp	Water Contact Material
Miscellaneous Process Devices/Components [G]			
1600-031SRP[1] [G]	N/A	CLD 23	MLTPL
1600-032S/25[2] [G]	N/A	CLD 23	MLTPL
1600-032SRP[1] [G]	N/A	CLD 23	MLTPL
1600-033SRP[1] [G]	N/A	CLD 23	MLTPL
1600-174SRP[1] [G]	N/A	CLD 23	MLTPL
1630-025SRP[3] [G]	N/A	CLD 23	MLTPL
1630-048SRP[3] [G]	N/A	CLD 23	MLTPL
1630-054SRP[3] [G]	N/A	CLD 23	MLTPL
1634-038S/25[2] [G]	N/A	CLD 23	MLTPL
HK-1[4]	1/2" x 1/2"	D. HOT	MLTPL
HLP-1 Hot-Link® Plus	[5]	D. HOT	MLTPL
HLS-1 Hot-Link® Bypass System	[5]	D. HOT	MLTPL

[1] The 1600-031SRP, 1600-032SRP, 1600-033SRP, and 1600-174SRP are replacement part flange sets, which include flanges and gaskets, for use in the 1600 and 1900 series pumps.

[2] The 1634-038S/25 and 1600-032S/25 are bulk orders of flange only sets.

[3] The 1630-025SRP, 1630-048SRP, and 1630-054SRP are replacement impeller parts for use with the 1600 series and 1900 series pumps.

[4] HK-1 flexible plumbing connectors are Certified as replacement parts for the HLS-1 Hot-Link® Bypass System and and HLP-1 Hot-Link® Plus.

[5] The HLS-1 Hot-Link® Bypass System and and HLP-1 Hot-Link® Plus consists of a 3/4" pump, 3/4" fitting, 1/2" valve, and 1/2" hoses.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state

laws and the U.S. Safe Drinking Water Act.

Pumps

00(X)-(1)(2)(3)(4)(5)-(6)[6] [G]	1/2" - 1 1/2"	D. HOT	MLTPL
121N[7] [G]	2 1/2"	CLD 23	MLTPL
122N[7] [G]	3"	CLD 23	MLTPL
131N[7] [G]	3"	CLD 23	MLTPL
132N[7] [G]	3"	CLD 23	MLTPL
133N[7] [G]	3"	CLD 23	MLTPL
138N[7] [G]	3"	CLD 23	MLTPL
1600N[7] [G]	1 1/2" - 2"	CLD 23	MLTPL
1610N[7] [G]	1 1/2"	CLD 23	MLTPL
1611N[7] [G]	1 1/2"	CLD 23	MLTPL
1612N[7] [G]	1 1/2"	CLD 23	MLTPL
1614N[7] [G]	1 1/2"	CLD 23	MLTPL
1615N[7] [G]	1 1/2"	CLD 23	MLTPL
1616N[7] [G]	1 1/2"	CLD 23	MLTPL
1619N[7] [G]	1 1/2"	CLD 23	MLTPL
1630-S33[7] [G]	1 1/2"	CLD 23	MLTPL
1630-S33PS[7] [G]	1 1/2"	CLD 23	MLTPL
1630-S34[7] [G]	1 1/2"	CLD 23	MLTPL
1630-S34PS[7] [G]	1 1/2"	CLD 23	MLTPL
1630-S41[7] [G]	1 1/2"	CLD 23	MLTPL
1630-S50[7] [G]	1 1/2"	CLD 23	MLTPL
1630N[7] [G]	1 1/2"	CLD 23	MLTPL
1632N[7] [G]	1 1/2"	CLD 23	MLTPL
1634N[7] [G]	1 1/2"	CLD 23	MLTPL
1635N[7] [G]	2"	CLD 23	MLTPL
1636N[7] [G]	2"	CLD 23	MLTPL
1638N[7] [G]	2"	CLD 23	MLTPL
1640N[7] [G]	2"	CLD 23	MLTPL
1641N[7] [G]	2"	CLD 23	MLTPL
1911N[7] [G]	1 1/2"	CLD 23	MLTPL
1915N[7] [G]	1 1/2"	CLD 23	MLTPL
1919N[7] [G]	1 1/2"	CLD 23	MLTPL
1935N[7] [G]	2"	CLD 23	MLTPL
1941N[7] [G]	2"	CLD 23	MLTPL
CI1206 Pump[G]	[10]	CLD 23	MLTPL
CI1207 Pump[G]	[10]	CLD 23	MLTPL
CI1209C Pump[G]	[10]	CLD 23	MLTPL
CI1506 Pump[G]	[10]	CLD 23	MLTPL
CI1507 Pump[G]	[10]	CLD 23	MLTPL
CI1509 Pump[G]	[10]	CLD 23	MLTPL
CI1509C Pump[G]	[10]	CLD 23	MLTPL
CI1511 Pump[G]	[10]	CLD 23	MLTPL
CI2007 Pump[G]	[10]	CLD 23	MLTPL
CI2009 Pump[G]	[10]	CLD 23	MLTPL

CI2009C Pump[G]	[10]	CLD 23	MLTPL
CI2506 Pump[G]	[10]	CLD 23	MLTPL
CI2507 Pump[G]	[10]	CLD 23	MLTPL
CI2508 Pump[G]	[10]	CLD 23	MLTPL
CI2509 Pump[G]	[10]	CLD 23	MLTPL
CI2509C Pump[G]	[10]	CLD 23	MLTPL
CI2510 Pump[G]	[10]	CLD 23	MLTPL
CI2510C Pump[G]	[10]	CLD 23	MLTPL
CI2511 Pump[G]	[10]	CLD 23	MLTPL
CI2513 Pump[G]	[10]	CLD 23	MLTPL
CI3007 Pump[G]	[10]	CLD 23	MLTPL
CI3009 Pump[G]	[10]	CLD 23	MLTPL
CI3009C Pump[G]	[10]	CLD 23	MLTPL
CI3011 Pump[G]	[10]	CLD 23	MLTPL
CI3013 Pump[G]	[10]	CLD 23	MLTPL
FI1206 Pump[G]	[10]	CLD 23	MLTPL
FI1207 Pump[G]	[10]	CLD 23	MLTPL
FI1506 Pump[G]	[10]	CLD 23	MLTPL
FI1507 Pump[G]	[10]	CLD 23	MLTPL
FI1509 Pump[G]	[10]	CLD 23	MLTPL
FI1511 Pump[G]	[10]	CLD 23	MLTPL
FI2007 Pump[G]	[10]	CLD 23	MLTPL
FI2009 Pump[G]	[10]	CLD 23	MLTPL
FI2506 Pump[G]	[10]	CLD 23	MLTPL
FI2507 Pump[G]	[10]	CLD 23	MLTPL
FI2508 Pump[G]	[10]	CLD 23	MLTPL
FI2509 Pump[G]	[10]	CLD 23	MLTPL
FI2510 Pump[G]	[10]	CLD 23	MLTPL
FI2511 Pump[G]	[10]	CLD 23	MLTPL
FI2513 Pump[G]	[10]	CLD 23	MLTPL
FI3007 Pump[G]	[10]	CLD 23	MLTPL
FI3009 Pump[G]	[10]	CLD 23	MLTPL
FI3011 Pump[G]	[10]	CLD 23	MLTPL
FI3013 Pump[G]	[10]	CLD 23	MLTPL
KS1506 Pump[G]	[10]	CLD 23	MLTPL
KS1507 Pump[G]	[10]	CLD 23	MLTPL
KS1509 Pump[G]	[10]	CLD 23	MLTPL
KS2006 Pump[G]	[10]	CLD 23	MLTPL
KS2007 Pump[G]	[10]	CLD 23	MLTPL
KS2009 Pump[G]	[10]	CLD 23	MLTPL
KS2011 Pump[G]	[10]	CLD 23	MLTPL
KS2508 Pump[G]	[10]	CLD 23	MLTPL
KS2510 Pump[G]	[10]	CLD 23	MLTPL
KS3006 Pump[G]	[10]	CLD 23	MLTPL
KS3007 Pump[G]	[10]	CLD 23	MLTPL
KS3009 Pump[G]	[10]	CLD 23	MLTPL
KS3011 Pump[G]	[10]	CLD 23	MLTPL
KS3013 Pump[G]	[10]	CLD 23	MLTPL
KV1506 Pump[G]	[10]	CLD 23	MLTPL
KV1507 Pump[G]	[10]	CLD 23	MLTPL

KV1509 Pump[G]	[10]	CLD 23	MLTPL
KV2006 Pump[G]	[10]	CLD 23	MLTPL
KV2007 Pump[G]	[10]	CLD 23	MLTPL
KV2009 Pump[G]	[10]	CLD 23	MLTPL
KV2011 Pump[G]	[10]	CLD 23	MLTPL
KV2508 Pump[G]	[10]	CLD 23	MLTPL
KV2510 Pump[G]	[10]	CLD 23	MLTPL
KV3006 Pump[G]	[10]	CLD 23	MLTPL
KV3007 Pump[G]	[10]	CLD 23	MLTPL
KV3009 Pump[G]	[10]	CLD 23	MLTPL
KV3011 Pump[G]	[10]	CLD 23	MLTPL
KV3013 Pump[G]	[10]	CLD 23	MLTPL
LoadMatch® L(A)-(B)(C)(D)(E)-(F)(G)(H)(I)[8] [G]	1/2" - 1 1/2"	D. HOT	MLTPL
VR1212-DY1-USXXXX[11]	3/4" - 1"	D. HOT	MLTPL

[6] (X) The first identification group is the pump series identifier: 3, 5, 6, 7, or 15

(1) Control modifier

IQ - Circulator with Smart Pulse Control
 MS - Multi speed circulator
 VR - Variable speed circulator, outdoor reset (VSD-R)
 VS - Variable speed circulator, set point (VSD-S)
 VV - Variable speed circulator, 0-10 volt (VSD-V)
 VT - Variable speed circulator, solar (VSD-T)
 VDT - Variable speed circulator, Delta-T (VSD-S)
 Z - Zoning circulator (115V/120V, 60 Hz versions only)
 No letter - No controller

(2) Material Modifier

B - Bronze casing
 S - Stainless steel casing
 Cast iron casings with no material modifier are excluded from this Certification.

(3) Casing modifier

No letter - Sweat pump housing connection
 C - Casing threads for body mounting
 E - End suction pump housing connections
 F - Flange pump housing connections
 T - Internal NPT pipe thread pump housing connections

(4) Revision version. Any value is acceptable.

(5) Motor modifier (last digit in 2nd identification group)

No letter - 115V, 60 Hz motor
 A - 220V, 50 Hz motor
 R - 100/110V, 50 Hz motor
 U - 265V, 60 Hz motor
 V - 220V, 60 Hz motor
 Y - 208/230V, 60 Hz motor

(6) Optional 3rd identification group

Blank
 IFC - Integral flow check
 PNP - Plumb 'n Plug

Any optional identifier not affecting the wetted parts

[7] All pump models may be supplied with or without flanges.

[8] (A) Model

0205, 0609, 0410, 0710

(B) Motor rating

Y6 - 110/120v, 60Hz

B6 - 220/240v, 60Hz

R6 - 265/277v, 60Hz

Y5 - 110/120v, 50Hz

B5 - 220/240v, 50Hz

R5 - 265/277v, 50Hz

(C) Casing material

B - Bronze

S - Stainless steel

(D) Feature

S - Standard

D - Variable speed 0 - 10V

E - Variable speed set point

M - 3 Speed (multi)

Z - Zoning circ.

I - IFC

R - Relay

F - Variable speed set point + IFC

N - 3 Speed (multi) + IFC

X - Zoning circ. + IFC

V - Variable speed 0 - 10V + IFC

(E) UL Version. Any value is acceptable

(F) Connection

F - Flange, pipe mounting

S - Sweat, pipe mounting

C - Sweat, casing mounting

U - Union, pipe mounting

N - NPT, pipe mounting

E - End Suction, pipe mounting

(G) Fitting

7 - 3/4"

5 - 1/2"

H - horizontal

V - vertical

(H) Pump and bracket position

A, B, C, D, E, F, G, H, J, K, L, M, N, P, Q, R, S, T, U, V, W

(I) Feature

N - None

V - Viton seals

L - Line cord (non-UL)

Other identifiers denoting non-standard changes

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

[10] Impeller size: 6" - 17"

[11] XXXX in the trade name refers to any alpha numeric character. They do not reflect wetted parts.

Valves

FB075-1[G]	3/4"	CLD 23	MLTPL
FB100-1[G]	1"	CLD 23	MLTPL
FB125-1[G]	1 1/4"	CLD 23	MLTPL
HLV-1 Hot-Link® Bypass Valve[G]	1/2"	D. HOT	MLTPL
V(x)C2D2(y)(z)[9] [G]	1/2" - 3/4"	D. HOT	MLTPL
WAGS7200-4[G]	3/4"	CLD 23	MLTPL

[9] V - Valve body

x - Size

050 - 1/2"

075 - 3/4"

C - Sweat connection

2 - Two way valve type

D - NSF 61 Sec. 8 and Annex G

2 - Revision Level

y - Non-wetted components

Blank - No actuator

8 digit alpha-numeric code - Actuator naming system

z - Bulk pack

Blank - Standard (1 unit)

BP - Bulk pack

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Number of matching Manufacturers is 1

Number of matching Products is 128

Processing time was 0 seconds